

www.sayfagroup.co.uk enquiries@sayfagroup.co.uk +44 (0) 1509 509 273

Certificate of Technical Conformity

Product Code(s)		Product Description(s)			
SGR.1050.1100.MF		SayfaGuard counterbalanced collective safety guard rail system. 1100mm finishing height from walking level and 470mm centres between and miniumum 76mm parapet / roof flashing.			
Material Specifications	6061-T6 Extruded Aluminium Horizontal Counter Balance 6061-T6 Extruded Aluminium Foot 6061-T6 Extruded Aluminium Rail Section A4/1.4401 A70 Grade M12 Bolts LDPE Nylon Inserts Concrete counter balance weights (18kg min) each.				
Installation / Fixings	Free standing, suitable for roofs with a maximum 5 deg. pitch. Dead load of 40kg per linear metre.				
Test Standards	- BS 13700:2021 Permanent counterweighted guardrail systems				
Related Standards	- BS 7883 Code of practice for the design, selection, installation, use and maintenance of anchor devices conforming to BS EN 795 - BS 6399: Part 2 1995 Wind Code - BS EN 13374:2013+A1:2018 Temporary edge protection systems. Product specification. Test methods				
Design Load Lateral	300N		Ultimate Load Lateral	495N	
Design Load Vertical	300N		Ultimate Load Parallel	1250)N
Assembly	Component Form, tool free and each section component 25kg or below				
Primary Test Criteria's	Observations				
Design Lateral	43mm. Pass.				
Design Vertical	40mm. Pass				
Ultimate Load Lateral	Pass				
Ultimate Load Parallel	Pass				
Corresion Test	Pass				
Design & Ergonomics	Pass				
Development Director	T King		Authorising Signature	Thing	27/10/2023









RHINODECK™ AIRDECK™ LOUVSOL™ EDGESEIL™ FALLSECURE™

Sayfa Group (Europe) Ltd is registered in England & Wales no. 11268889. Registered office: $\label{thm:continuous} \mbox{Unit B1 - Research Point, Shepshed, Loughborough, Leicestershire, LE12~9NH.}$



Private & Confidential, no disclosure or circulation without prior agreement.